

Batteries



00	41 1	100	J.
36 1	Monthe	Warranty	π
JU I	MOHUIS	vvarianty	

*for PRIVATE passenger vehicle use, subject to terms and conditions

PART NUMBER DIN55MF CHARACTERISTIC Lead-Acid Sealed Maintenance Free GROUP SIZE LB2/DIN55 Material Polypropylene (PP) Handle 1-pc PP handle

Case Colour	Black Casing
Lid Colour	Blue Lid
Ledge / Hold-down	Recessed ledge on all sides
Vent	Centralized venting

Revision No. 00

Release Date: May 2025

		IFICAT	

OVERALL DIMENSIONS	METRIC (mm)
LENGTH	242
WIDTH	175
HEIGHT (bottom to top cover)	175
TOTAL HEIGHT (bottom to top of terminal)	175
NOMINAL WEIGHT	13.41 kg


TERMINAL DATA	POSITIVE	NEGATIVE	
TYPE	SAE	SAE	
TERMINAL HEIGHT (mm)	18.5±1.50	18.5±1.50	
BOTTOM DIAMETER (mm)	19.5+0/-0.3	17.5+0/-0.3	
TAPER	1:9	1:9	
POLARITY	000000 - +		

TECHNICAL SPECIFICATIONS

	550 CCA
COLD CRANKING AMPS	Test reference:
(CCA)	AS60095.1: 2022
	Rated CCA DCH
	at 18°C for 30 sec
	100 mins
	Test reference:
CAPACITY (RC)	AS60095.1: 2022
	25 Amps DCH
	at 10.5 V cut-off voltage


	60 AH
AMPERE-HOUR (20-HOUR CAPACITY)	Test reference: AS60095.1: 2022
	Rated AH DCH at 10.5 V cut-off
PLATE DESIGN	Lead-Calcium Alloy Full Frame Plate Design
ELECTROLYTE	36% H2SO4 at 15°C

TOP VIEW



FRONT VIEW

CASE AND LID



SIDE VIEW

