

Batteries



96 1		Warranty	*
5 M I	WITCHES		V AM
	MOHUIS	vvallalii	v

*for PRIVATE passenger vehicle use, subject to terms and conditions

PART NUMBER	U1LMF	
CHARACTERISTIC	Lead-Acid Sealed Maintenance Free	
GROUP SIZE	GU1	
	Material	Polypropylene (PP)
	Handle	1-pc PP handle
	Case Colour	Black Casing
CASE AND LID	Lid Colour	Black Lid
	Ledge / Hold-down	None

Vent

Revision No. 00

Release Date: May 2025

Centralized venting

DIMENSIONAL SPECIFICATIONS			
OVERALL DIMENSIONS	METRIC (mm)		
LENGTH	196		
WIDTH	128		
HEIGHT (bottom to top cover)	159		
TOTAL HEIGHT (bottom to top of terminal)	184		
NOMINAL WEIGHT	8.95kg		

TERMINAL DATA	POSITIVE	NEGATIVE
TYPE	U1	U1
TERMINAL HEIGHT (mm)	23.5±1.50	23.5±1.50
POLARITY	000	+

TECHNICAL SPECIFICATIONS		
	350 CCA	
COLD CRANKING AMPS (CCA)	Test reference: AS60095.1: 2022 Rated CCA DCH at 18°C for 30 sec	
	45 mins	
CAPACITY (RC)	Test reference: AS60095.1: 2022 25 Amps DCH at 10.5 V cut-off voltage	

	35 AH
AMPERE-HOUR (20-HOUR CAPACITY)	Test reference: AS60095.1: 2022
	Rated AH DCH at 10.5 V cut-off
PLATE DESIGN	Lead-Calcium Alloy Full Frame Plate Design
ELECTROLYTE	36% H2SO4 at 15°C





