



36 Months Warranty*

*for PRIVATE passenger vehicle use, subject to terms and conditions

DIMENSIONAL SPECIFICATIONS

OVERALL DIMENSIONS	METRIC (mm)
LENGTH	242
WIDTH	175
HEIGHT (bottom to top cover)	190
TOTAL HEIGHT (bottom to top of terminal)	190
NOMINAL WEIGHT	18.8 kg

PART NUMBER	SSAGM-55EU	
CHARACTERISTIC	Valve Regulated Lead Acid (Absorbent Glass Mat)	
GROUP SIZE	N55H/LN2	
CASE AND LID	Material	Polypropylene (PP)
	Handle	1-pc PP handle
	Case Colour	Black Casing
	Lid Colour	Black Lid
	Ledge / Hold-down	End Ledge & Front Ledge (EL & FL)
	Vent	Centralized venting

TERMINAL DATA	POSITIVE	NEGATIVE
TYPE	SAE	SAE
TERMINAL HEIGHT (mm)	18.5±1.50	18.5±1.50
BOTTOM DIAMETER (mm)	19.5±0.3	17.5±0.3
TAPER	1:9	1:9
POLARITY		

TECHNICAL SPECIFICATIONS

COLD CRANKING AMPS (CCA)	680* CCA	AMPERE-HOUR (20-HOUR CAPACITY)	60 AH
	Test reference: AS60095.1: 2022 Rated CCA DCH at 18°C for 30 sec		Test reference: AS60095.1: 2022 Rated AH DCH at 10.5 V cut-off
CAPACITY (RC)	100 mins	PLATE DESIGN	Lead-Calcium Alloy Full Frame Plate Design
	Test reference: AS60095.1: 2022 25 Amps DCH at 10.5 V cut-off voltage	ELECTROLYTE	36% H2SO4 at 15°C

