




24 Months Warranty*

*for PRIVATE passenger vehicle use, subject to terms and conditions

DIMENSIONAL SPECIFICATIONS

OVERALL DIMENSIONS	METRIC (mm)
LENGTH	237
WIDTH	171
HEIGHT (bottom to top cover)	182
TOTAL HEIGHT (bottom to top of terminal)	208
NOMINAL WEIGHT	15.92 kg

PART NUMBER	MSDP22	
CHARACTERISTIC	Lead-Acid (Enhanced Flooded Battery)	
GROUP SIZE	A46	
CASE AND LID	Material	Polypropylene (PP)
	Handle	1-pc PP handle
	Case Colour	Black Casing
	Lid Colour	Black Lid
	Ledge / Hold-down	End Ledge & Front Ledge (EL & FL)
	Vent	Centralized venting

TERMINAL DATA	POSITIVE	NEGATIVE
TYPE	Dual Fit Align (DFA)	Dual Fit Align (DFA)
TERMINAL HEIGHT (mm)	24.0±0.20	24.0±0.20
BOTTOM DIAMETER (mm)	20.1±0.20	18.5±0.20
TAPER	1:9	1:9
POLARITY		

TECHNICAL SPECIFICATIONS

COLD CRANKING AMPS (CCA)	525 CCA	AMPERE-HOUR (20-HOUR CAPACITY)	60 AH
	Test reference: AS60095.1: 2022 Rated CCA DCH at 18°C for 30 sec		Test reference: AS60095.1: 2022 Rated AH DCH at 10.5 V cut-off
CAPACITY (RC)	100 mins	PLATE DESIGN	Lead-Calcium Alloy Full Frame Plate Design
	Test reference: AS60095.1: 2022 25 Amps DCH at 10.5 V cut-off voltage	ELECTROLYTE	36% H2SO4 at 15°C

