



OP34M

12V 800CCA BLUE TOP MARINE AGM BATTERY

Battery Model: 34M

Part Number: 8006-252

Nominal Voltage: 12 volts

NSN: 6140 01 475 9416

Description: High power, sealed lead acid, marine starting battery

Features:

- Both dual-purpose and starting applications available
- Up to 3x more recharges than other marine batteries
- More than 15 times the vibration resistance
- Spill-proof
- Mountable in virtually any position
- Maintenance-free
- Optimal starting power (dual purpose and starting applications available)
- Works well as a boat battery or RV battery
- Patented Spiralcell Technology® means more running time, faster recharge, and up to twice the life of traditional marine and RV batteries.

Physical Characteristics:

Plate Design:	High purity lead-tin alloy. Wound cell configuration utilizing proprietary <i>SPIRALCELL</i> ® technology.	
Electrolyte:	Sulfuric acid, H ₂ SO ₄	
Case:	Polypropylene	
Color:	Case:	Dark Gray
	Cover:	"OPTIMA" Blue
Group Size:	BCI: 34	

	Standard	Metric
Length:	10.018"	254.46 mm
Width:	6.829"	173.46 mm
Height:	7.925"	201.30 mm (Height at the top of terminals)
Weight:	38.4 lb	17.4 kg

Terminal Configuration: SAE / BCI automotive and 5/16"-18UNC-2A threaded stainless steel stud.

Performance Data:

Open Circuit Voltage (Fully charged):	12.8 volts
Internal Resistance (Fully charged):	.0030 ohms
Capacity:	50 Ah (C/20)
Reserve Capacity:	BCI: 100 minutes
	(25 amp discharge, 80°F (26.7°C), to 10.5 volts cut-off)

Power:

CCA (BCI 0°F):	800 amps
MCA (BCI 32°F):	1000 amps



Mackay ph 4957 6123 | Townsville ph 4774 7344

Recommended Charging:

The following charging methods are recommended to ensure a long battery life: (Always use a voltage regulated charger with voltage limits set as described below.)

Model: 34M

These batteries are designed for engine starting applications. They are not recommended or warranted for use in deep cycle applications.

Recommended Charging Information:

Alternator:	13.3 to 15.0 volts
Battery Charger (Constant Voltage):	13.8 to 15.0 volts; 10 amps maximum; 6-12 hours approximate
Float Charge:	13.2 to 13.8 volts; 1 amp maximum; (indefinite time at lower voltages)
Rapid Recharge:	Maximum voltage 15.6 volts. No current limit as long as battery
(Constant voltage charger)	temperature remains below 125°F (51.7°C). Charge until current drops below 1 amp.
All limits must be strictly adhered to.	

Always wear safety glasses when working with batteries.

Always use a voltage regulated battery charger with limits set to the above ratings. Overcharging can cause the safety valves to open and battery gases to escape, causing premature end of life. These gases are flammable! You cannot replace water in sealed batteries that have been overcharged. Any battery that becomes very hot while charging should be disconnected immediately.

Not fully charging a battery can result in poor performance and a reduction in capacity.

