



OPD35YT

12V 620CCA YELLOW TOP DEEP CYCLE AGM BATTERY

Battery Model: D35

Part Number: 8040-222

Nominal Voltage: 12 volts

NSN: Number applied for, product currently available

Description: High power, dual purpose engine start and deep cycle, sealed lead acid battery

Features:

- Deep-cycle and cranking power
- Up to 3X longer life
- 15 times more vibration-resistant
- Virtually spill-proof
- Mountable in virtually any position
- Maintenance-free
- Faster recharging
- Optimal starting power
- 300+ discharge/recharge cycles
- Patented Spiralcell Technology®

Physical Characteristics:

Plate Design: High purity lead-tin alloy. Wound cell configuration utilizing proprietary *SPIRALCELL*® technology.

Electrolyte: Sulfuric acid, H₂SO₄

Case: Polypropylene

Color: Case: Light Gray
Cover: "OPTIMA" Yellow

Group Size: BCI: 35

	Standard	Metric
Length:	9.340"	237.24 mm
Width:	6.700"	170.18 mm
Height:	7.685"	195.20 mm (Height at the top of terminals)
Weight:	36.4 lb	16.5 kg

Terminal Configuration: SAE / BCI automotive.

Performance Data:

Open Circuit Voltage (Fully charged): 13.1 volts

Internal Resistance (Fully charged): .0030 ohms

Capacity: 48 Ah (C/20)

Reserve Capacity: BCI: 100 minutes
(25 amp discharge, 80°F (26.7°C), to 10.5 volts cut-off)

Power:

CCA (BCI 0°F): 620 amps

MCA (BCI 32°F): 770 amps



Mackay ph 4957 6123 | Townsville ph 4774 7344

Recommended Charging:

The following charging methods are recommended to ensure a long battery life: (Always use a voltage regulated charger with voltage limits set as described below.)

Model: D35

These batteries are designed for starting and deep cycle applications and for use in vehicles with large accessory loads.

Recommended Charging Information:

Alternator:	13.65 to 15.0 volts
Battery Charger (Constant Voltage):	13.8 to 15.0 volts; 10 amps maximum; 6-12 hours approximate
Float Charge:	13.2 to 13.8 volts; 1 amp maximum; (indefinite time at lower voltages)
Rapid Recharge:	Maximum voltage 15.6 volts. No current limit as long as battery temperature remains below 125°F (51.7°C). Charge until current drops below 1 amp.
(Constant voltage charger)	
Cyclic or Series String Applications:	14.7 volts. No current limit as long as battery temperature remains below 125°F (51.7°C). When current falls below 1 amp, finish with 2 amp constant current for 1 hour.
	All limits must be strictly adhered to.

Always wear safety glasses when working with batteries.

Always use a voltage regulated battery charger with limits set to the above ratings. Overcharging can cause the safety valves to open and battery gases to escape, causing premature end of life. These gases are flammable! You cannot replace water in sealed batteries that have been overcharged. Any battery that becomes very hot while charging should be disconnected immediately.

Not fully charging a battery can result in poor performance and a reduction in capacity.

