

### Technical Information

The Predator PMF50ZZL is a group 24 size, sealed maintenance free starting battery. Produced to the highest quality standards by one of the leading South Korean battery manufacturers, the Predator PMF50ZZL has been designed with durability, performance and value in mind.

#### Features and Benefits include:

- Calcium-Calcium, 99.99% pure lead expanded grid plates
- Unique high density active material on plates
- Centre cast on straps - more durable and efficient
- Built in hydrometer
- Heat sealed leak proof cover
- Patented liquid & gas separators to prevent electrolyte loss
- Flame arrestors on vents
- Low resistance envelope separators
- High strength polypropylene case



### Applications

|                            |
|----------------------------|
| Agricultural machinery     |
| Earth Moving Equipment     |
| Light commercial equipment |
| Passenger cars             |
| 4x4                        |

### Specifications

|                                |                         |                              |                                       |
|--------------------------------|-------------------------|------------------------------|---------------------------------------|
| Battery Type:                  | Sealed Maintenance Free | Container Material / Colour: | Polypropylene / Black                 |
| Voltage:                       | 12 V                    | Lid Type / Colour:           | Sealed / Black                        |
| Capacity (@20hr rate):         | 80                      | Plate Type:                  | Expanded Metal Grid                   |
| Cold Cranking Amps -18°C, SAE: | 600                     | Separator Type:              | Low Resistance - Microporous Envelope |
| Reserve Capacity:              | 135 minutes             | Assembly Layout:             | 0 (RH Positive)                       |
| Overall Dimensions:            | L 260 x W 176 x H 225   | Terminal Type:               | SAE                                   |
| Wet Battery Weight:            | 18.5 kg                 | BCI Group:                   | Group 24                              |