MPPT AUTOMATIC SOLAR CHARGE CONTROLLERS

The 40A is ideal for solar systems that are larger and require faster charging. Ideally suited to larger caravans and RVs, these sophisticated MPPT solar controllers ensure a solar system is delivering the optimal power to meet a wide range of power demands.

40 AMP 12 / 24 VOLT







KEY FEATURES

MULTI-CHEMISTRY

Set the charge profile to suit battery types; Wet, AGM, GEL or Lithium



Touch screen buttons and bright screen ensures the controller looks great no matter where it's placed

SOLAR CONTROLLER

98.2% efficient MPPT (Maximum Power Point Tracking) solar controller maximizes the sun's radiation and converts it to power

TEMPERATURE SENSOR

Plug-in sensor enables unit to optimise charge performance and offer additional protection

PREMIUM QUALITY

Tempered glass cover with housing made from cast aluminium providing premium feel with silent operation













SPECIFICATIONS

PART NO.	SC440			
INPUT	12V or 24V			
MAX INPUT	100Vdc , 40A			
MAX CHARGE/LOAD	40A			
MAX PANEL SIZE	600W (12V) / 1200W (24V)			
LOAD SWITCHING	Negative			
BATTERY	12V or 24V			
CHARGE CONTROL	4 Stage Charging		12V	24V
	Bulk/	Gel	14.2V	28.4V
	Absorption	AGM	14.4V	28.8V
		Wet	14.6V	29.2V
		Lithium	14.2V	28.4V
	Equalisation	Gel	-	-
		AGM	14.6V	29.2V
		Wet	14.8V	29.6V
		Lithium	-	-
	Float	Gel	-	-
		AGM	13.8V	27.6V
		Wet	-	-
		Lithium	-	-
STANDBY CURRENT	10mA			
APPROVAL	EMC			
IP RATING	IP34			







Replacement Parts: **SC400D** Remote Control Display **SC4TMP** External temperature sensor probe