

# BLUETTI Premium 200 V2 Portable Power Station | 2700W 2073.6Wh

- **High-Capacity Power:** With 2,073.6Wh capacity and 2,700W output
- **Versatile Applications:** Powers up to 7 devices simultaneously
- **Advanced Battery Management:** Monitors battery performance in real-time
- **TurboBoost Charging:** Reaching 80% charge in just 1.1 hours
- **Built for Safety:** Feel confident with automotive-grade battery cells and a robust safety system
- **5-year warranty**



## Specifications

### BATTERY INFO

Capacity:	2073.6Wh (54Ah)
Type:	LiFePO4
Life Cycles:	6,000+ Cycles to 80% Original Capacity
Shelf-life:	Recharge to 40%-60% Every 3-6 Months

# OUTPUT

AC Outlets:	2,700W in total, 230V, 11.3A
Inverter Type:	Pure Sine Wave
Lifting Power:	3900W
USB-C Port:	2 x 100W Max.
USB-A Port:	2 x 15W, 5V / 3A
DC Outlets:	1 x 12V/10A (Car Outlet)

# INPUT

AC Input:	2,300W Max.
Solar Input:	1,000W Max., 12V to 60V, 20A Max.
Car Input:	96W (12V) / 192W (24V)
Max Input:	2,400W Max. (AC + DC Input)



- |                       |  |
|-----------------------|--|
| 1 DC Power Button     | 7 Circuit Breaker                      |
| 2 LCD Display         | 8 AC Input                             |
| 3 Power Button        | 9 USB-A Ports                          |
| 4 AC Power Button     | 10 USB-C Ports                         |
| 5 AC Outlet           | 11 Cigarette Lighter Port (Car Outlet) |
| 6 Grounding Terminal* | 12 DC input                            |

GENERAL

Pass-through Charging:	Yes
App Control:	WiFi/Bluetooth
Scalability:	No
Weight:	24.2 kg (53.35lbs)
Dimensions (LxWxD):	350×250×323.6mm (13.78 x 9.84 x 12.74 in)
Charging Temperature:	0°C to 40°C (32°F to 104°F)
Discharging Temperature:	-20°C to 40°C (-4°F to 104°F)
Storage Temperature:	Up to 1 month: -10°C to 40°C (14°F to 104°F) More than 1 month: -10°C to 35°C (14°F to 95°F)
Warranty:	5 Years